



Typ	EVO 170 AC/DC	EVO 200 AC/DC	EVO 250 320 AC/DC	EVO 400 AC/DC
Netzspannung, 1/3-ph. 400V/50Hz [V/Hz]	230V/50Hz	230V/50Hz.	400V/50Hz.	400V/50Hz
Netzabsicherung (träge) [A]	16	16	16 32	32
Einstellungen	digital stufenlos	digital stufenlos	digital stufenlos	digital stufenlos
Leerlaufspannung V	62	65	70	70
Einstellbereich min/max	5 - 170 A	5 - 200 A	5 - 250 A 5-320 A	5 - 400 A
Schweißstrom ED [A/%]	170 A / 35 %	200 A / 35 %	250 A / 35 % 320 A / 35 %	400 A / 35 %
Pulsfrequenz [Hz]	1 - 500 Hz.	1 - 500 Hz	1 - 500 Hz	1 - 500 Hz
empf. Elektr. Durchmesser [mm]	E 1,0-3,2; WIG 1,0-2,4	E 1,0-4,0; WIG 1,0-3,2	E 1,0-4,0(5.0); WIG 1,0-4,2	E 1,0-4,0(5.0); WIG 1,0-4,2
Kühlart	F	F	F	F
Isolierklasse	F	F	F	F
Schutzart IP (IEC 529)	23	23	23	23
Maße ca. (LxBxH) [mm]	430 x 220 x 340	430 x 220 x 340	580 x 280 x 490	580 x 280 x 490
Gewicht [kg]	14	15	29 35	40
Artikelnummer	13990	13991	13994 13992	13993