



TYP	CONNEXX 300 MW / 300MKW VPM	CONNEXX 350 MW / 350MKW VPM wassergekühlt	CONNEXX 450 MW / 450MK VPM wassergekühlt
Netzspannung [V/Hz]	400/50	400/50	400/50
Netzabsicherung [A]	16	25	30
Einstellbereich	25- 350	450	550
Leerlaufspannung [V]	65 max.	65 max.	65 max.
Einstellbereich [A/V]	25 - 250A	25 - 350 A	25 - 40 A
Schweißstrom ED [A/%]	300 A/60 %	350 A/60 %	450 A/65 %
Pulsfrequenz	25 - 250 Hz	25 - 250 Hz	25 - 250 Hz
Drahtdurchmesser [mm]	0.8 - 1.0 (1.2)	0.8 - 1.2	0.8 - 1.6
Vorschub	4-Rollen verzahnt	Al 4-Rollen verzahnt	Al 4-Rollen verzahnt ,140 Watt
Brenner	Zentr. 36	Zentr. 401 D	Zentr. 501 D
Kühlart	F	F	F
Isolierklasse	F	F	F
Schutzart IP (IEC 529)	21	21	21
Maße [mm]	870 x 420 x 820	850 x 420 x 620	850 x 420 x 620
Gewicht [kg]	82	125	170
Artikelnummer	30001 30002	30010 30011	30021