



| Typ | 180 L | 180 LT | 200 L | 200 LT |
|-----------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|
| Netzspannung, 1/3-ph [V/Hz] | 230/50 1-ph. / 400/50 2-ph. | 230/50 1-ph. / 400/50 2-ph. | 230/50 1-ph. / 400/50 2-ph. | 230/50 1-ph. / 400/50 2-ph. |
| Netzabsicherung (träge) [A] | 230 V/16 A 400 V /20 A | 230 V/16 A 400 V /20 A | 230 V/16 400 V/20 | 230 V/16 400 V/25 |
| Regelbereich [A] | 25-180 | 25-180 | 25-200 | 25-200 |
| Schweißstrom bei 230 V | 25 - 140 | 25 - 140 | 25 - 140 | 25 - 140 |
| Schweißstrom bei 400 V | 60 - 180 | 60-180 | 80-200 | 80-200 |
| Schweißstrom ED [A/%] | 180 A /15 % | 230 A /35 % | 260 A /35 % | 300 A /35 % |
| Zündspannung [V] | 44 V, max. | 46 V, max. | 68 V, max. | 68 V, max. |
| Kühlart | F | F | F | F |
| Isolierklasse | F | F | F | F |
| Schutzart IP (IEC 529) | 21 | 21 | 21 | 21 |
| Maße ca. (LxBxH) [mm] | 470 x 275 x 385 | 470 x 275 x 385 | 470 x 275 x 385 | 470 x 275 x 385 |
| Gewicht [kg] | 27 | 28 | 30 | 31 |
| Artikelnummer | 03312 | 03313 | 03314 | 03315 |