



TYP	210 Co 210 Co-IP	250 A 250 A-IP	270/7 A 270/7 A-IP 4R	300 A 300 A-IP 4R	Lotus 200 löten + schweißen
Netzspannung [V/Hz]	umschaltbare 230/50 1-ph. 400/50 2-ph.	400/50	400/50	400/50	400/50
Netzabsicherung [A]	16	16	16	16	16
Einstellungen	6+6	7	7	2*7	7+7
Leerlaufspannung [V]	14 - 26	17-37	17-39	18-44	13 - 36
Einstellbereich [A/V]	25-160 A / 60-210 A	25-250 A / 15-26 V	25-270 A / 15,5-27 V	30-300 A / 16-29 V	15-200 A / 13-36 V
Schweißstrom ED [A/%]	125A/35% - 200A/35%	150 A/100% - 250 A/35 %	160 A/100% - 270 A/35 %	170 A/100% - 300 A/35 %	125A/100% - 200A/35%
Drahtdurchmesser [mm]	0.6 -0.8 (1,0)	0.6 - 1,0 (1,2)	(0.6) 0,8 - 1,0	(0.6) 0,8 - 1,	2 0.6 - 0,8 (1,0)
Vorschub	Al 2-R	Al 2-R	Al 2-R Al 4-R	Al 2-R Al 4-R	Al 2-R verzahnt
Brenner	Zentr. 15	Zentr. 25	Zentr. 25	Zentr. 25	Zentr. 25
Kühlart	F	F	F	F	F
Isolierklasse	F	F	F	F	F
Schutzart IP (IEC 529)	21	21	21	21	21
Maße [mm]	810 x 325 x 560				
Gewicht [kg]	50	850 x 420 x 620	850 x 420 x 620	850 x 420 x 620	810 x 325 x 560
Artikelnummer	01578 01056	01590 01592	21007 21009	01591 B1594	01572