



TYP	320/35   320/35-IP	320/60   320/60-IP	350/35   350/35-IP	DIGI-MIG350/35-IP	DIGI-MIG 350/60   350/60-IP	DIGI-MIG450/60   450/60-IP
Netzspannung [V/Hz]	400/50	400/50	400/50	400/50	400/50	400/50
Netzabsicherung [A]	16	20	25	25	25	30
Einstellungen	2 x 7	2 x 7	4 x 7	4 x 7	4 x 7	2 x 7
Leerlaufspannung [V]	18 - 44	18 - 46	20 - 49	20 - 49	20 - 49	20 - 50
Einstellbereich [A/V]	30-320 A/16-30 V	30-320 A/16-30 V	40-400 A/16-33 V	40-400 A/16-33 V	45-400 A/16-33 V	50-500 A/16,5-35 V
Schweißstrom ED [A/%]	180 A/100% - 320 A/35 %	220 A/100% - 320 A/60 %	230 A/100% - 350 A/35 %	230 A/100% - 350 A/35 %	260 A/100% - 350 A/60 %	300 A/100% - 450 A/60 %
Drahtdurchmesser [mm]	(0,6) 0,8 - 1,2	(0,6) 0,8 - 1,2	0,8 - 1,2	0,8 - 1,2	0,8 - 1,2	0,8 - 1,6
Vorschub	Al 2-Rollen verzahnt	Al 2-Rollen verzahnt	Al 2-Rollen verzahnt	Al 4-Rollen verzahnt	Al 4-Rollen verzahnt	Al 4-Rollen verzahnt
Brenner	Zentr. 25	Zentr. 25   Zentr. 36	Zentr. 36	Zentr. 36	Zentr. 36	Zentr. 36
Kühlart	F	F	F	F	F	F
Isolierklasse	F	F	F	F	F	F
Schutzart IP (IEC 529)	21	21	21	21	21	21
Maße [mm]	870 x 420 x 820	870 x 420 x 820	870 x 420 x 620	920 x 520 x 820	920 x 520 x 820	920 x 520 x 820
Gewicht [kg]	105	115	125	135	145	155
Artikelnummer	21013   21014	21015   21016	21017   21018	21400	21019   21020	21021   21022