



TYP	M W 320/60 320/60-IP	MW DIGI-MIG MW 350/35 350/35-IP	MW DIGI-MIG MW 350/60 350/60-IP	MW DIGI-MIG MW 450/60 450/60-IP
Netzspannung [V/Hz]	400/50	400/50	400/50	400/50
Netzabsicherung [A]	20	20	20	20
Einstellungen	2 x 7	4 x 7	4 x 7	4 x 7
Leerlaufspannung [V]	18 - 46	20 - 49	20 - 49	20 - 50
Einstellbereich [A/V]	30-320 A/16-30 V	40-400 A/16-33 V	45-400 A/16-33 V	50-500 A/16,5-35 V
Schweißstrom ED [A/%]	220 A/100% - 320 A/60 %	230 A/100% - 350 A/35%	260 A/100% - 350 A/60 %	300 A/100% - 450 A/60 %
Drahtdurchmesser [mm]	(0,6) 0,8 - 1,2	0,8 - 1,2	0,8 - 1,6	0,8 - 1,6
Vorschub	Al 2-Rollen verzahnt	Al 4-Rollen verzahnt	Al 4-Rollen verzahnt	Al 4-Rollen verzahnt
Brenner	Zentr. 36	Zentr. 36	Zentr. 36	Zentr. 36
Kühlart	F	F	F	F
Isolierklasse	F	F	F	F
Schutzart IP (IEC 529)	21	21	21	21
Maße [mm]	920 x 520 x 820	920 x 520 x 820	920 x 520 x 820	920 x 520 x 820
Gewicht [kg]	135	155	165	175
Artikelnummer	21025 21026	21029 21030	21031 21032	21035 21036