

D+L TECHNIK



TYP	GK 350	GK 450	GKW 350	GKW 450	GKW 550
Netzspannung [V/Hz]	400/50	400/50	400/50	400/50	400/50
Netzabsicherung [A]	25	30	25	30	30
Einstellungen	2 x 7	4 x 7	4 x 7	4 x 7	4 x 7
Leerlaufspannung [V]	20 - 49	20 - 49	20 - 49	20 - 50	20 - 52
Einstellbereich [A/V]	45-400 A/16-33 V	50-500 A/16,5-35 V	45-400 A/16-33 V	50-500 A/16,5-35 V	55-600 A/16,5-39 V
Schweißstrom ED [A/%]	260 A/100% - 350 A/60 %	300 A/100% - 450 A/60 %	260 A/100% - 350 A/60 %	300 A/100% - 450 A/60 %	380 A/100% - 550 A/60
Drahtdurchmesser [mm]	0,8 - 1,2	0,8 - 1,2	0,8 - 1,2	0,8 - 1,2	0,8 - 1,6
Vorschub	Al 2-RZ / 140 Watt	Al 2-RZ / 140 Wa	Al 2-RZ / 140 Watt	Al 4-RZ / 140 Wa	Al 4-RZ / 140 Wat
Brenner	Z 36 KD	Z 36 KD	Zentr. 401	Zentr. 401	Zentr. 501
Kühlart	F	F	F	F	F
Isolierklasse	F	F	F	F	F
Schutzart IP (IEC 529)	21	21	21	21	21
Maße [mm]	1000 x 600 x 1340	1000 x 600 x 1340	1000 x 600 x 1340	1000 x 600 x 1340	1000 x 600 x 1340
Gewicht [kg]	170	185	190	205	220
Artikelnummer	01522	01524	01530	01533	01534